Cc:	Nonresponsive Based on revised scope @tetratech.com]
To:	Nonresponsive Based on revised scope
From:	Wagner, Christine[/O=EXCHANGELABS/OU=EXCHANGE ADMINISTRATIVE GROUP OF THE CONTROL
Sent:	Fri 6/11/2021 3:35:14 PM (UTC)
Subject:	Re: Property 1 power line
Thanks	CONTRACT OF BRIDE TO A CONTRACT OF THE STATE
	nk we want to exclude any areas within 50 feet because of the ditch line
50 I tilli	ink we want to excited any areas within 30 feet because of the ditentine
Thank y	you
Chris	
1	On Jun 11, 2021, at 11:15 AM, Nonresponsive Based on revised scope @tetratech.com> wrote:
,	Chris,
	According to OSHA 1926.1408 (h) the right of way minimum clearance distance for high voltage overhead power lines
	over 500 kV is 35 feet. Dominion Energy high voltage power lines running along Bailey Memorial Hwy are 500 kV or
į	greater. Dominion requires 30-50ft right of way clearance on those high voltage power lines.
,	We will see al. for any CIC was also and each that add adds the call at the call at the call.
	We will work for our GIS people and get that added to the collector map today for you.
	Thanks,
Ī.	
i.	<u>_</u>
ī	
<u>,<u>l</u></u>	Nonresponsive Based on revised scope Environmental Scientist
Ĺ	Nonresponsive Based on revised scope <u>atternates to the com</u>
	Tetra Tech Complex World, Clear Solutions™ Northeast Operations
	1777 Sentry Parkway West Ridg 12 Suite 102 Rive Rell. DA 10422 tetratech com

1/// Sentry Parkway West, Bldg. 12 | Suite 102 | Blue Bell, PA 19422 | tetratech.com